

## CROPLANDS PART NUMBERS: 5880-3/4-2TOC10 BOOMJET NOZZLE TWIN



**5880-3/4 NPT Female**  
Back inlet connection.  
Weight: Brass 0.91 kg.

Type 5880 BoomJet nozzle is used for spraying areas not easily accessed with a boom sprayer. It combines two off-center tips and three VeeJet® nozzles to produce an overall wide swath flat spray. The nozzle assembly provides good distribution considering the wide pattern coverage obtained; however, the uniformity is not as good as with a properly operated boom sprayer.\* Supplied with one additional ¼" NPT pipe plug and one blank tip for setting BoomJet to one side only. Also has a ¼" NPT pressure gauge port.

\*Uniformity can be optimized by double overlapping spray swaths on successive sprayer passes. Remember, this also doubles the application volume.

### How to order:

Specify BoomJet nozzle number.  
Example: 5880-3/4-2TOC-06



W = Maximum effective coverage with nozzle mounted at 1 m height.

	(2)	(2)	(1)	bar	l/min	"W" (meters)	l/ha				
							6 km/h	8 km/h	12 km/h	16 km/h	24 km/h
5880-3/4-2TOC06	6733-OC06	H1/4VV-1506	H1/4VWL-9502 with 50 mesh strainer	1.5	7.26	10.2	71.2	53.4	35.6	26.7	17.8
				2.0	8.38	10.3	81.4	61.0	40.7	30.5	20.3
				2.5	9.37	10.5	89.2	66.9	44.6	33.5	22.3
5880-3/4-2TOC10	OC10	H1/4U-0508HE	H1/4VWL-11004 with 50 mesh strainer	1.5	11.16	12.0	93.0	69.8	46.5	34.9	23.3
				2.0	12.89	12.1	107	79.9	53.3	39.9	26.6
				2.5	14.41	12.3	117	87.9	58.6	43.9	29.3
5880-3/4-2TOC20	OC20	H1/4U-0520HE	H1/4VWL-9506 with 50 mesh strainer	1.5	24.00	14.3	168	126	83.9	62.9	42.0
				2.0	27.72	15.2	182	137	91.2	68.4	45.6
				2.5	30.99	15.8	196	147	98.1	73.6	49.0
5880-3/4-2TOC40	OC40	H1/4U-0540HE	H1/4U-9510	1.5	47.44	17.1	277	208	139	104	69.4
				2.0	54.78	18.2	301	226	150	113	75.2
				2.5	61.25	19.2	319	239	160	120	79.8

Note: Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C).